

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Revision Date 19.02.2019

Version 21.9

SECTION 1. Identification of the substance/mixture and of the company/undertaking**1.1 Product identifier**

Catalogue No.	100983
Product name	Ethanol absolute for analysis EMSURE® ACS,ISO,Reag. Ph Eur
REACH Registration Number	01-2119457610-43-XXXX
CAS-No.	64-17-5

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses	Reagent for analysis, Chemical production In compliance with the conditions described in the annex to this safety data sheet.
-----------------	---

1.3 Details of the supplier of the safety data sheet

Company	Merck KGaA * 64271 Darmstadt * Germany * Phone:+49 6151 72-0
Responsible Department	LS-QHC * e-mail: prodsafe@merckgroup.com

1.4 Emergency telephone number **Please contact the regional company representation in your country.****SECTION 2. Hazards identification****2.1 Classification of the substance or mixture**
Classification (REGULATION (EC) No 1272/2008)

Flammable liquid, Category 2, H225

Eye irritation, Category 2, H319

For the full text of the H-Statements mentioned in this Section, see Section 16.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Catalogue No.
Product name

100983
Ethanol absolute for analysis EMSURE® ACS,ISO,Reag. Ph Eur

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms



Signal word

Danger

Hazard statements

H225 Highly flammable liquid and vapour.

H319 Causes serious eye irritation.

Precautionary statements

Prevention

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources.

No smoking.

P240 Ground/bond container and receiving equipment.

Response

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes.

Remove contact lenses, if present and easy to do. Continue rinsing.

Storage

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.

Reduced labelling (≤125 ml)

Hazard pictograms



Signal word

Danger

Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Index-No. 603-002-00-5

2.3 Other hazards

None known.

SECTION 3. Composition/information on ingredients

3.1 Substance

Formula	C ₂ H ₅ OH	C ₂ H ₆ O (Hill)
Index-No.	603-002-00-5	

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Catalogue No. 100983
Product name Ethanol absolute for analysis EMSURE® ACS,ISO,Reag. Ph Eur

EC-No. 200-578-6
Molar mass 46,07 g/mol

Hazardous components (REGULATION (EC) No 1272/2008)

Chemical name (Concentration)

CAS-No. Registration Classification
number

ethanol (<= 100 %)

Substance does not meet the criteria for PBT or vPvB according to Regulation (EC) No 1907/2006, Annex XIII.

64-17-5 01-2119457610-
43-XXXX Flammable liquid, Category 2, H225
Eye irritation, Category 2, H319

For the full text of the H-Statements mentioned in this Section, see Section 16.

3.2 Mixture

Not applicable

SECTION 4. First aid measures

4.1 Description of first aid measures

After inhalation: fresh air.

In case of skin contact: Take off immediately all contaminated clothing. Rinse skin with water/ shower.

After eye contact: rinse out with plenty of water. Call in ophthalmologist. Remove contact lenses.

After swallowing: immediately make victim drink water (two glasses at most). Consult a physician.

4.2 Most important symptoms and effects, both acute and delayed

irritant effects, respiratory paralysis, Dizziness, narcosis, inebriation, euphoria, Nausea, Vomiting

4.3 Indication of any immediate medical attention and special treatment needed

No information available.

SECTION 5. Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

Carbon dioxide (CO₂), Foam, Dry powder, Water

Unsuitable extinguishing media

For this substance/mixture no limitations of extinguishing agents are given.

5.2 Special hazards arising from the substance or mixture

Combustible.

Pay attention to flashback.

Forms explosive mixtures with air at ambient temperatures.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Catalogue No. 100983
Product name Ethanol absolute for analysis EMSURE® ACS,ISO,Reag. Ph Eur

Vapours are heavier than air and may spread along floors.
Development of hazardous combustion gases or vapours possible in the event of fire.

5.3 Advice for firefighters

Special protective equipment for firefighters

In the event of fire, wear self-contained breathing apparatus.

Further information

Remove container from danger zone and cool with water. Prevent fire extinguishing water from contaminating surface water or the ground water system.

SECTION 6. Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Advice for non-emergency personnel: Do not breathe vapours, aerosols. Avoid substance contact. Ensure adequate ventilation. Keep away from heat and sources of ignition. Evacuate the danger area, observe emergency procedures, consult an expert.

Advice for emergency responders:

Protective equipment see section 8.

6.2 Environmental precautions

Do not let product enter drains. Risk of explosion.

6.3 Methods and materials for containment and cleaning up

Cover drains. Collect, bind, and pump off spills. Observe possible material restrictions (see sections 7 and 10). Take up with liquid-absorbent material (e.g. Chemizorb®). Dispose of properly. Clean up affected area.

6.4 Reference to other sections

Indications about waste treatment see section 13.

SECTION 7. Handling and storage

7.1 Precautions for safe handling

Advice on safe handling

Observe label precautions.

Advice on protection against fire and explosion

Keep away from open flames, hot surfaces and sources of ignition. Take precautionary measures against static discharge.

Hygiene measures

Change contaminated clothing. Wash hands after working with substance.

7.2 Conditions for safe storage, including any incompatibilities

Storage conditions

Keep container tightly closed in a dry and well-ventilated place. Keep away from heat and sources of ignition.

Recommended storage temperature see product label.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Catalogue No. 100983
Product name Ethanol absolute for analysis EMSURE® ACS,ISO,Reag. Ph Eur

7.3 Specific end use(s)

See exposure scenario in the Annex to this MSDS.

SECTION 8. Exposure controls/personal protection

8.1 Control parameters

Derived No Effect Level (DNEL)

Worker DNEL, acute	Local effects	inhalation	1900 mg/m ³
Worker DNEL, longterm	Systemic effects	dermal	343 mg/kg Body weight
Worker DNEL, longterm	Systemic effects	inhalation	950 mg/m ³
Consumer DNEL, acute	Local effects	inhalation	950 mg/m ³
Consumer DNEL, longterm	Systemic effects	dermal	206 mg/kg Body weight
Consumer DNEL, longterm	Systemic effects	inhalation	114 mg/m ³
Consumer DNEL, longterm	Systemic effects	oral	87 mg/kg Body weight

Predicted No Effect Concentration (PNEC)

PNEC Fresh water	0,96 mg/l
PNEC Marine water	0,79 mg/l
PNEC Fresh water sediment	3,6 mg/kg
PNEC Soil	0,63 mg/kg
PNEC Aquatic intermittent release	2,75 mg/l
PNEC Sewage treatment plant	580 mg/l
PNEC oral	720 mg/kg

8.2 Exposure controls

Engineering measures

Technical measures and appropriate working operations should be given priority over the use of personal protective equipment.

See section 7.1.

Individual protection measures

Protective clothing needs to be selected specifically for the workplace, depending on concentrations and quantities of the hazardous substances handled. The chemical resistance of the protective equipment should be enquired at the respective supplier.

Eye/face protection

Safety glasses

Hand protection

full contact:

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Catalogue No. 100983
Product name Ethanol absolute for analysis EMSURE® ACS,ISO,Reag. Ph Eur

Glove material: butyl-rubber
Glove thickness: 0,7 mm
Break through time: > 480 min

splash contact:

Glove material: Nitrile rubber
Glove thickness: 0,40 mm
Break through time: > 120 min

The protective gloves to be used must comply with the specifications of EC Directive 89/686/EEC and the related standard EN374, for example KCL 898 Butoject® (full contact), KCL 730 Camatril® -Velours (splash contact).

The breakthrough times stated above were determined by KCL in laboratory tests acc. to EN374 with samples of the recommended glove types.

This recommendation applies only to the product stated in the safety data sheet, supplied by us and for the designated use. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN374 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell, Internet: www.kcl.de).

Other protective equipment

Flame retardant antistatic protective clothing.

Respiratory protection

required when vapours/aerosols are generated.

Recommended Filter type: Filter A (acc. to DIN 3181) for vapours of organic compounds

The entrepreneur has to ensure that maintenance, cleaning and testing of respiratory protective devices are carried out according to the instructions of the producer.

These measures have to be properly documented.

Environmental exposure controls

Do not let product enter drains.

Risk of explosion.

SECTION 9. Physical and chemical properties

9.1 Information on basic physical and chemical properties

Form	liquid
Colour	colourless
Odour	alcohol-like
Odour Threshold	0,1 - 5058,5 ppm
pH	7,0 at 10 g/l 20 °C
Melting point	-114,5 °C

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Catalogue No. 100983
Product name Ethanol absolute for analysis EMSURE® ACS,ISO,Reag. Ph Eur

Boiling point/boiling range	78,3 °C at 1.013 hPa
Flash point	12 °C Method: c.c.
Evaporation rate	No information available.
Flammability (solid, gas)	No information available.
Lower explosion limit	3,1 %(V)
Upper explosion limit	27,7 %(V)
Vapour pressure	59 hPa at 20 °C
Relative vapour density	1,6
Density	0,790 - 0,793 g/cm ³ at 20 °C
Relative density	No information available.
Water solubility	at 20 °C completely miscible
Partition coefficient: n-octanol/water	log Pow: -0,31 (experimental) (Lit.) Bioaccumulation is not expected.
Auto-ignition temperature	No information available.
Decomposition temperature	No information available.
Viscosity, dynamic	1,2 mPa.s at 20 °C
Explosive properties	Not classified as explosive.
Oxidizing properties	none

9.2 Other data

Ignition temperature	425 °C Method: DIN 51794
Conductivity	< 1 µS/cm

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Catalogue No.
Product name

100983
Ethanol absolute for analysis EMSURE® ACS,ISO,Reag. Ph Eur

SECTION 10. Stability and reactivity

10.1 Reactivity

Vapours may form explosive mixture with air.

10.2 Chemical stability

The product is chemically stable under standard ambient conditions (room temperature) .

10.3 Possibility of hazardous reactions

Risk of explosion/exothermic reaction with:

hydrogen peroxide, perchlorates, perchloric acid, Nitric acid, mercury(II) nitrate, permanganic acid, Nitriles, peroxy compounds, Strong oxidizing agents, nitrosyl compounds, Peroxides, sodium, Potassium, halogen oxides, calcium hypochlorite, nitrogen dioxide, metallic oxides, uranium hexafluoride, iodides, Chlorine, Alkali metals, Alkaline earth metals, alkali oxides, Ethylene oxide

silver, with, Nitric acid

silver compounds, with, Ammonia

potassium permanganate, with, conc. sulfuric acid

Risk of ignition or formation of inflammable gases or vapours with:

halogen-halogen compounds, chromium(VI) oxide, chromyl chloride, Fluorine, hydrides, Oxides of phosphorus, platinum

Nitric acid, with, potassium permanganate

10.4 Conditions to avoid

Warming.

10.5 Incompatible materials

rubber, various plastics

10.6 Hazardous decomposition products

no information available

SECTION 11. Toxicological information

11.1 Information on toxicological effects

Acute oral toxicity

LD50 Rat: 10.470 mg/kg

OECD Test Guideline 401

Symptoms: Nausea, Vomiting

Acute inhalation toxicity

LC50 Rat: 124,7 mg/l; 4 h ; vapour

OECD Test Guideline 403

Symptoms: slight mucosal irritations

Acute dermal toxicity

This information is not available.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Catalogue No. 100983
Product name Ethanol absolute for analysis EMSURE® ACS,ISO,Reag. Ph Eur

Skin irritation

Rabbit

Result: No skin irritation

OECD Test Guideline 404

Repeated or prolonged exposure may cause skin irritation and dermatitis, due to degreasing properties of the product.

Eye irritation

Rabbit

Result: Eye irritation

OECD Test Guideline 405

Causes serious eye irritation.

Sensitisation

Local lymph node assay (LLNA) Mouse

Result: negative

Method: OECD Test Guideline 429

Germ cell mutagenicity

Genotoxicity in vitro

Ames test

Salmonella typhimurium

Result: negative

Method: OECD Test Guideline 471

In vitro mammalian cell gene mutation test

Mouse lymphoma test

Result: negative

Method: OECD Test Guideline 476

Carcinogenicity

This information is not available.

Reproductive toxicity

Application Route: Oral

Mouse

Method: OECD Test Guideline 416

Teratogenicity

This information is not available.

Specific target organ toxicity - single exposure

This information is not available.

Specific target organ toxicity - repeated exposure

This information is not available.

Aspiration hazard

This information is not available.

11.2 Further information

Systemic effects:

euphoria

After absorption:

Dizziness, inebriation, narcosis, respiratory paralysis

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Catalogue No. 100983
Product name Ethanol absolute for analysis EMSURE® ACS,ISO,Reag. Ph Eur

Other dangerous properties can not be excluded.
Handle in accordance with good industrial hygiene and safety practice.

SECTION 12. Ecological information

12.1 Toxicity

Toxicity to fish

flow-through test EC50 Pimephales promelas (fathead minnow): 15.300 mg/l; 96 h

Analytical monitoring: yes

US-EPA

Toxicity to daphnia and other aquatic invertebrates

EC50 Daphnia magna (Water flea): 9.268 - 14.221 mg/l; 48 h
(IUCLID)

Toxicity to algae

IC5 Scenedesmus quadricauda (Green algae): 5.000 mg/l; 7 d
(Lit.)

Toxicity to bacteria

EC5 Pseudomonas putida: 6.500 mg/l; 16 h
(IUCLID)

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity)

semi-static test NOEC Daphnia magna (Water flea): 9,6 mg/l; 9 d
(ECHA)

12.2 Persistence and degradability

Biodegradability

94 %

OECD Test Guideline 301E

Readily biodegradable

Biochemical Oxygen Demand (BOD)

930 - 1.670 mg/g (5 d)

(Lit.)

Theoretical oxygen demand (ThOD)

2.100 mg/g

(Lit.)

Ratio COD/ThBOD

90 %

(Lit.)

12.3 Bioaccumulative potential

Partition coefficient: n-octanol/water

log Pow: -0,31

(experimental)

(Lit.) Bioaccumulation is not expected.

12.4 Mobility in soil

No information available.

12.5 Results of PBT and vPvB assessment

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Catalogue No. 100983
Product name Ethanol absolute for analysis EMSURE® ACS,ISO,Reag. Ph Eur

Substance does not meet the criteria for PBT or vPvB according to Regulation (EC) No 1907/2006, Annex XIII.

12.6 Other adverse effects

Additional ecological information

No interference with wastewater treatment plants are to be expected when used properly.

Discharge into the environment must be avoided.

SECTION 13. Disposal considerations

Waste treatment methods

See www.retrologistik.com for processes regarding the return of chemicals and containers, or contact us there if you have further questions.

SECTION 14. Transport information

Land transport (ADR/RID)

14.1 UN number	UN 1170
14.2 Proper shipping name	ETHANOL
14.3 Class	3
14.4 Packing group	II
14.5 Environmentally hazardous	--
14.6 Special precautions for user	yes
Tunnel restriction code	D/E

Inland waterway transport (ADN)

Not relevant

Air transport (IATA)

14.1 UN number	UN 1170
14.2 Proper shipping name	ETHANOL
14.3 Class	3
14.4 Packing group	II
14.5 Environmentally hazardous	--
14.6 Special precautions for user	no

Sea transport (IMDG)

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Catalogue No. 100983
Product name Ethanol absolute for analysis EMSURE® ACS,ISO,Reag. Ph Eur

14.1 UN number UN 1170
14.2 Proper shipping name ETHANOL
14.3 Class 3
14.4 Packing group II
14.5 Environmentally hazardous --
14.6 Special precautions for user yes
EmS F-E S-D

14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code
Not relevant

SECTION 15. Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulations

Major Accident Hazard Legislation SEVESO III
FLAMMABLE LIQUIDS
P5c
Quantity 1: 5.000 t
Quantity 2: 50.000 t

Occupational restrictions Take note of Dir 94/33/EC on the protection of young people at work.

Regulation (EC) No 1005/2009 on substances that deplete the ozone layer not regulated

Regulation (EC) No 850/2004 of the European Parliament and of the Council of 29 April 2004 on persistent organic pollutants and amending Directive 79/117/EEC not regulated

Substances of very high concern (SVHC) This product does not contain substances of very high concern according to Regulation (EC) No 1907/2006 (REACH), Article 57 above the respective regulatory concentration limit of $\geq 0.1\%$ (w/w).

National legislation

Storage class 3

15.2 Chemical safety assessment

For this product a chemical safety assessment was not carried out.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Catalogue No. 100983
Product name Ethanol absolute for analysis EMSURE® ACS,ISO,Reag. Ph Eur

SECTION 16. Other information

Full text of H-Statements referred to under sections 2 and 3.

H225 Highly flammable liquid and vapour.
H319 Causes serious eye irritation.

Training advice

Provide adequate information, instruction and training for operators.

Labelling

Hazard pictograms



Signal word

Danger

Hazard statements

H225 Highly flammable liquid and vapour.
H319 Causes serious eye irritation.

Precautionary statements

Prevention

P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.

P240 Ground/bond container and receiving equipment.

Response

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes.

Remove contact lenses, if present and easy to do. Continue rinsing.

Storage

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.

Key or legend to abbreviations and acronyms used in the safety data sheet

Used abbreviations and acronyms can be looked up at www.wikipedia.org.

Regional representation

This information is given on the authorised Safety Data Sheet for your country.

The information contained herein is based on the present state of our knowledge. It characterises the product with regard to the appropriate safety precautions. It does not represent a guarantee of any properties of the product.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Catalogue No. 100983
Product name Ethanol absolute for analysis EMSURE® ACS,ISO,Reag. Ph Eur

EXPOSURE SCENARIO 1 (Industrial use)

1. Industrial use Reagent for analysis, Chemical production)

Sectors of end-use

- SU 3* Industrial uses: Uses of substances as such or in preparations at industrial sites
SU9 Manufacture of fine chemicals
SU 10 Formulation [mixing] of preparations and/ or re-packaging (excluding alloys)

Chemical product category

- PC19* Intermediate
PC21 Laboratory chemicals

Process categories

- PROC1* Use in closed process, no likelihood of exposure
PROC2 Use in closed, continuous process with occasional controlled exposure
PROC3 Use in closed batch process (synthesis or formulation)
PROC4 Use in batch and other process (synthesis) where opportunity for exposure arises
PROC5 Mixing or blending in batch processes for formulation of preparations and articles (multistage and/ or significant contact)
PROC8a Transfer of substance or preparation (charging/ discharging) from/ to vessels/ large containers at non-dedicated facilities
PROC8b Transfer of substance or preparation (charging/ discharging) from/ to vessels/ large containers at dedicated facilities
PROC9 Transfer of substance or preparation into small containers (dedicated filling line, including weighing)
PROC10 Roller application or brushing
PROC14 Production of preparations or articles by tableting, compression, extrusion, pelletisation
PROC15 Use as laboratory reagent

Environmental Release Categories

- ERC1* Manufacture of substances
ERC2 Formulation of preparations
ERC4 Industrial use of processing aids in processes and products, not becoming part of articles
ERC6a Industrial use resulting in manufacture of another substance (use of intermediates)
-

2. Contributing scenarios: Operational conditions and risk management measures

2.1 Contributing scenario controlling environmental exposure for: ERC1, ERC4, ERC6a

Amount used

Annual amount per site 400000 t

Environment factors not influenced by risk management

Flow rate 18.000 m3/d

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Catalogue No. 100983
Product name Ethanol absolute for analysis EMSURE® ACS,ISO,Reag. Ph Eur

Other given operational conditions affecting environmental exposure

Number of emission days per year 350
Emission or Release Factor: Air 70 %
Emission or Release Factor: Water 87 %

Conditions and measures related to municipal sewage treatment plant

Type of Sewage Treatment Plant Municipal sewage treatment plant
Effectiveness (of a measure) 90 %

2.2 Contributing scenario controlling environmental exposure for: ERC2

Amount used

Annual amount per site 75000 t

Environment factors not influenced by risk management

Flow rate 18.000 m³/d

Other given operational conditions affecting environmental exposure

Number of emission days per year 300

Conditions and measures related to municipal sewage treatment plant

Type of Sewage Treatment Plant Municipal sewage treatment plant
Effectiveness (of a measure) 90 %

2.3 Contributing scenario controlling worker exposure for: PROC1, PROC2, PROC3, PROC4, PROC5, PROC8a, PROC8b, PROC9, PROC10, PROC14, PROC15

Product characteristics

Concentration of the Substance in Mixture/Article Covers the percentage of the substance in the product up to 100 % (unless stated differently).
Physical Form (at time of use) High volatile liquid

Frequency and duration of use

Frequency of use 8 hours/day

Other operational conditions affecting workers exposure

Outdoor / Indoor Indoor without local exhaust ventilation (LEV)

Additional good practice advice beyond the REACH Chemical Safety Assessment

Additional good practice advice Wear suitable gloves (tested to EN374) and eye protection.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Catalogue No. 100983
Product name Ethanol absolute for analysis EMSURE® ACS,ISO,Reag. Ph Eur

3. Exposure estimation and reference to its source

Environment

CS	Use descriptor	Msafe	Compartment	RCR	Exposure Assessment Method
2.1	ERC1		Fresh water	< 0,01	ECETOC TRA
			Marine water	< 0,01	ECETOC TRA
			Soil	< 0,01	ECETOC TRA
2.1	ERC4		Fresh water	< 0,01	ECETOC TRA
			Marine water	< 0,01	ECETOC TRA
			Soil	< 0,01	ECETOC TRA
2.1	ERC6a		Fresh water	< 0,01	ECETOC TRA
			Marine water	< 0,01	ECETOC TRA
			Soil	< 0,01	ECETOC TRA
2.2	ERC2		Fresh water	0,11	ECETOC TRA
			Marine water	0,01	ECETOC TRA
			Soil	< 0,01	ECETOC TRA

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Catalogue No. 100983
 Product name Ethanol absolute for analysis EMSURE® ACS,ISO,Reag. Ph Eur

Workers

CS	Use descriptor	Exposure duration, route, effect	RCR	Exposure Assessment Method
2.3	PROC1	longterm, inhalative, systemic	< 0,01	ECETOC TRA 3
		longterm, dermal, systemic	< 0,01	ECETOC TRA 3
		longterm, combined, systemic	< 0,01	
2.3	PROC2	longterm, inhalative, systemic	0,05	ECETOC TRA 3
		longterm, dermal, systemic	< 0,01	ECETOC TRA 3
		longterm, combined, systemic	0,05	
2.3	PROC3	longterm, inhalative, systemic	0,10	ECETOC TRA 3
		longterm, dermal, systemic	< 0,01	ECETOC TRA 3
		longterm, combined, systemic	0,10	
2.3	PROC4	longterm, inhalative, systemic	0,20	ECETOC TRA 3
		longterm, dermal, systemic	0,02	ECETOC TRA 3
		longterm, combined, systemic	0,22	
2.3	PROC5	longterm, inhalative, systemic	0,50	ECETOC TRA 3
		longterm, dermal, systemic	0,04	ECETOC TRA 3
		longterm, combined, systemic	0,54	
2.3	PROC8a	longterm, inhalative, systemic	0,50	ECETOC TRA 3
		longterm, dermal, systemic	0,04	ECETOC TRA 3
		longterm, combined, systemic	0,54	
2.3	PROC8b	longterm, inhalative, systemic	0,30	ECETOC TRA 3
		longterm, dermal, systemic	0,04	ECETOC TRA 3
		longterm, combined, systemic	0,34	
2.3	PROC9	longterm, inhalative, systemic	0,40	ECETOC TRA 3
		longterm, dermal, systemic	0,02	ECETOC TRA 3
		longterm, combined, systemic	0,42	
2.3	PROC10	longterm, inhalative, systemic	0,50	ECETOC TRA 3
		longterm, dermal, systemic	0,08	ECETOC TRA 3
		longterm, combined, systemic	0,58	
2.3	PROC14	longterm, inhalative, systemic	0,50	ECETOC TRA 3
		longterm, dermal, systemic	0,01	ECETOC TRA 3
		longterm, combined, systemic	0,51	
2.3	PROC15	longterm, inhalative, systemic	0,10	ECETOC TRA 3
		longterm, dermal, systemic	< 0,01	ECETOC TRA 3
		longterm, combined, systemic	0,10	

The default parameters and -efficiencies of the applied exposure assessment model were used for the calculation (unless stated differently).

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Catalogue No. 100983
Product name Ethanol absolute for analysis EMSURE® ACS,ISO,Reag. Ph Eur

4. Guidance to Downstream User to evaluate whether he works inside the boundaries set by the Exposure Scenario

Please refer to the following documents: ECHA Guidance on information requirements and chemical safety assessment Chapter R.12: Use descriptor system; ECHA Guidance for downstream users; ECHA Guidance on information requirements and chemical safety assessment Part D: Exposure Scenario Building, Part E: Risk Characterisation and Part G: Extending the SDS; VCI/Cefic REACH Practical Guides on Exposure Assessment and Communications in the Supply Chain; CEFIC Guidance Specific Environmental Release Categories (SPERCs).

For scaling of worker exposure assessments performed with ECETOC TRA, please consult the Merck tool ScIDeEx® at www.merckmillipore.com/scideex.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Catalogue No. 100983
Product name Ethanol absolute for analysis EMSURE® ACS,ISO,Reag. Ph Eur

EXPOSURE SCENARIO 2 (Professional use)

1. Professional use Reagent for analysis, Chemical production)

Sectors of end-use

SU 22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

Chemical product category

PC21 Laboratory chemicals

Process categories

PROC15 Use as laboratory reagent

Environmental Release Categories

ERC2 Formulation of preparations

ERC6a Industrial use resulting in manufacture of another substance (use of intermediates)

2. Contributing scenarios: Operational conditions and risk management measures

2.1 Contributing scenario controlling environmental exposure for: ERC2

Amount used

Annual amount per site 75000 t

Environment factors not influenced by risk management

Flow rate 18.000 m3/d

Other given operational conditions affecting environmental exposure

Number of emission days per year 300

Conditions and measures related to municipal sewage treatment plant

Type of Sewage Treatment Plant Municipal sewage treatment plant
Effectiveness (of a measure) 90 %

2.2 Contributing scenario controlling environmental exposure for: ERC6a

Amount used

Annual amount per site 400000 t

Environment factors not influenced by risk management

Flow rate 18.000 m3/d

Other given operational conditions affecting environmental exposure

Number of emission days per year 350
Emission or Release Factor: Air 70 %

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Catalogue No. 100983
Product name Ethanol absolute for analysis EMSURE® ACS,ISO,Reag. Ph Eur

Emission or Release Factor: 87 %
Water

Conditions and measures related to municipal sewage treatment plant

Type of Sewage Treatment Municipal sewage treatment plant
Plant
Effectiveness (of a measure) 90 %

2.3 Contributing scenario controlling worker exposure for: PROC15

Product characteristics

Concentration of the Substance in Mixture/Article Covers the percentage of the substance in the product up to 100 % (unless stated differently).
Physical Form (at time of use) High volatile liquid

Frequency and duration of use

Frequency of use 8 hours/day

Other operational conditions affecting workers exposure

Outdoor / Indoor Indoor without local exhaust ventilation (LEV)

Additional good practice advice beyond the REACH Chemical Safety Assessment

Additional good practice advice Wear suitable gloves (tested to EN374) and eye protection.

3. Exposure estimation and reference to its source

Environment

CS	Use descriptor	Msafe	Compartment	RCR	Exposure Assessment Method
2.1	ERC2		Fresh water	0,11	ECETOC TRA
			Marine water	0,01	ECETOC TRA
			Soil	< 0,01	ECETOC TRA
2.2	ERC6a		Fresh water	< 0,01	ECETOC TRA
			Marine water	< 0,01	ECETOC TRA
			Soil	< 0,01	ECETOC TRA

Workers

CS	Use descriptor	Exposure duration, route, effect	RCR	Exposure Assessment Method
2.3	PROC15	longterm, inhalative, systemic	0,10	ECETOC TRA 3
		longterm, dermal, systemic	< 0,01	ECETOC TRA 3
		longterm, combined, systemic	0,10	

The default parameters and -efficiencies of the applied exposure assessment model were used for the calculation (unless stated differently).

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Catalogue No. 100983
Product name Ethanol absolute for analysis EMSURE® ACS,ISO,Reag. Ph Eur

4. Guidance to Downstream User to evaluate whether he works inside the boundaries set by the Exposure Scenario

Please refer to the following documents: ECHA Guidance on information requirements and chemical safety assessment Chapter R.12: Use descriptor system; ECHA Guidance for downstream users; ECHA Guidance on information requirements and chemical safety assessment Part D: Exposure Scenario Building, Part E: Risk Characterisation and Part G: Extending the SDS; VCI/Cefic REACH Practical Guides on Exposure Assessment and Communications in the Supply Chain; CEFIC Guidance Specific Environmental Release Categories (SPERCs).

For scaling of worker exposure assessments performed with ECETOC TRA, please consult the Merck tool ScIDeEx® at www.merckmillipore.com/scideex.

The branding on the header and/or footer of this document may temporarily not visually match the product purchased as we transition our branding. However, all of the information in the document regarding the product remains unchanged and matches the product ordered. For further information please contact mlsbranding@sial.com.